

TeddyPardo

DualTeddyCap

Power Supplies Owner's manual



TeddyPardo

Before connecting your DualTeddyCap

The **TeddyCap power supply family** was designed to power Naim Audio pre amplifiers, CD players, headphone amplifiers, active crossovers, phono stages, etc. They replace the original products: HiCap, FlatCap, SuperCap and XPS.

Please follow your Naim Audio product owner's manual for the corresponding connection diagram.

Note that according to the Naim Audio schema, power amplifiers should be connected to the power supply rather than to the pre amplifier. Failing to do so may damage the power supply and/or the power amplifier.

Mains Power

The power supply should be connected to the mains via a standard cable with an IEC plug. For safety reasons it is preferable to use cables with molded plugs. The power supply should be connected to a grounded mains socket.

Fuses

The power supply is equipped with a fuse that resides in a small drawer on the IEC socket situated on the rear panel. Use only "slow blow" fuse for replacement.

We are not great fans of "Audiophile Fuses". Nevertheless, if you plan on using them, you should consider 30% higher rating

Use the following table to select the appropriate fuse value:

Power supply

220-240V 110-120V

TeddyCap

315-400mA 680-1000mA

TeddyCapPlus

315-400mA 680-1000mA

DualTeddyCap

400-680mA 800-1000mA

TeddyXPS

800-1000mA 1600-2000mA

TeddySuperCap

400-680mA 800-1000mA

TeddyPardo

Before connecting the power supply

Switching On

In order to switch on and off your power supply use the power switch situated on the rear panel. Best performance will be achieved when leaving the system switched on for long periods. Power consumption of the power supplies is in the order of few tens of Watts. The green LED indicates POWER ON.

Cables

The cables which are supplies with the power supply are not directional. It is however a good practice not to change the cable direction once installed and burned-in.

In order to keep the connectors clean it is recommended to disconnected and reconnect the plugs several times every 3-4 months. This operation will clean oxidation and dirt from the plugs and sockets. Always switch off your power supply before connecting or disconnecting cables

Burn in

The power supply requires a burn-in period of at least one week, during the first month the sound will continue to improve gradually. Note also that the internal capacitors need about 30 minutes until they are fully charged and perform optimally.

Specifications

Product	TeddyCap	TeddyCapPlus	DualTeddyCap	TeddyXPS
Outputs	2 x 24V 300mA	2 x 24V 300mA 18V 300mA	2 x 24V 300mA 2 x 24V 300mA 18V 300mA	±22V 300mA ±10V 300mA 2 x 15V 1A
Dimensions (H x W x D, mm)	57 x 169 x 243			
Mains	110-120V or 220-240V, 50/60Hz			

Conformity

Manufacturer Teddy Pardo, Hod Hasharon Israel
Products TeddyCap, TeddyCapPlus, DualTeddyCap, TeddyXPS, TeddySuperCap
Safety EN 60065

TeddyPardo


DualTeddyCap

Power Supplies Owner's manual

04	42.5-Stageline
05	CD5X-Stageline
06	NAC72-CD3.5
07	NAC72-Naxo2-4
08	NAC82
09	NAC152XS
10	NAC202-CD5XS
11	NAC202-Headline
12	NAC202-Stageline
13	NAC202
14	NAC282
15	SuperNait3
16	SuperNait3-Headline


DualTeddyCap

42.5 - Stageline - Headline



* This cable is optional extra
**Option "High quality 18V for Naim HeadLine"

DualTeddyCap CD5XS-Stageline



* This cable is optional extra

DualTeddyCap
NAC72-CD3.5




DualTeddyCap
NAC72-Naxo2-4




DualTeddyCap

NAC82




DualTeddyCap

NAC152XS




DualTeddyCap
NAC202 - CD5XS




DualTeddyCap

NAC202 - Headline





* This cable is optional extra

DualTeddyCap
NAC202 - Stageline




* This cable is optional extra





DualTeddyCap

SuperNait3




*4PIN DIN

5PIN DIN

* This cable is optional extra

DualTeddyCap

SuperNait3 - Headline



* This cable is optional extra